

1 RESPONSIBLE ORGANIZATION		LINEAR MOTION TYPE MOTOR OPERATED VALVE ASSEMBLY Device Specification					6 SPECIFICATION IDENTIFICATIONS			
2							7 Document no			
3							8 Latest revision		Date	
4							9 Issue status			
5							10			
11 VALVE BODY AND BONNET						75 ACTUATOR Continuation				
12	Body type		76	Motor contactor type						
13	Bonnet style		77	Motor thermal protection						
14	Inlet conn nominal size	Rating	78	Motor phase protection						
15	Outlet conn nominal size	Rating	79							
16	End conn termn type	Style	80 CONTROL MODE							
17	Flange facing finish		81	Enclosure type						
18	Stem seal type		82	Operation style						
19	Face-to-face standard		83	Input signal type						
20	Yoke boss diameter		84	Enclosure type no/class						
21	Body and bonnet material		85	Control mode						
22	Lining material		86	Digital communication std						
23	Body/Bonnet bolting matl		87	Internal power supply						
24	Packing flg bolting matl		88	Space heating						
25	Gasket material		89	Output speed control						
26	Packing material		90	Actuator control power						
27	Bellows seal material		91	Open/Close control						
28			92	Local/Stop/Remote cont						
29	VALVE TRIM		93	Local operator interface						
30	Closure member type		94	Signal termination type						
31	Trim style		95	Cert/Approval type						
32	Inherent characteristic		96	ESD control mode						
33	Seat ring type		97	Failure/Diagnostic action						
34	Flow direction force		98	Interlock/Inhibit mode						
35	Port/Orifice diameter		99	Diagnostics capabilities						
36	Stem diameter	Rt trawl	100	Motor reversal protection						
37	Closure member material		101	Enclosure material						
38	Seat ring material		102	Hardware material						
39	Stem material		103							
40	Cage material		104							
41	Guide/Retainer material		105 POSITION SWITCH OR TRANSMITTER							
42	Guide bushing material		106	Output signal type						
43	Hard facing/coating		107	Sensor style						
44			108	Contacts ac rating	At max					
45	GEAR REDUCER		109	Contacts dc rating	At max					
46	Gear reducer type		110	Signal power source						
47	Position lock style		111	Contacts arrangement	Quantity					
48	Nominal size		112	Integral indicator style						
49	Mounting base form size	Standard	113	Position light colors						
50	Output nominal speed		114							
51	Handwheel gear ratio		115 TORQUE SWITCH OR TRANSMITTER							
52	Gearbox ratio		116	Output signal type						
53	Rated output torque	Thrust	117	Sensor style						
54	Linear speed		118	Contacts ac rating	At max					
55	Manual operator type		119	Contacts dc rating	At max					
56	Stem coupling style		120	Signal power source						
57	Stem nominal diameter	Lead of screw	121	Contacts arrangement	Quantity					
58	Handwheel diameter		122	Integral indicator style						
59	Handwheel orientation		123	Protection feature						
60	Travel stops		124							
61	Bevel pinion material		125 AUXILIARY INPUTS AND OUTPUTS							
62	Bevel gear matl		126	Configuration type						
63	Housing material		127	Aux signal type						
64	Bushing/Coupling/Nut matl		128	Output signal type						
65	Lubricant material		129	Status contacts ac rating	At max					
66			130	Status contacts dc rating	At max					
67			131	Alarm contacts ac rating	At max					
68	ACTUATOR		132	Alarm contacts dc rating	At max					
69	Actuator type		133	Input signal power source						
70	Motor style		134	Output signal pwr source						
71	Motor nominal speed	number of poles	135	Status contacts arr	Quantity					
72	Power supply		136	Alarm contacts arr	Quantity					
73	Insulation class rating		137							
74	Motor phase style		138							
Rev	Date	Revision Description	By	Appv1	Appv2	Appv3	REMARKS			

1	RESPONSIBLE ORGANIZATION				LINEAR MOTION TYPE MOTOR OPERATED VALVE ASSEMBLY Device Specification				6	SPECIFICATION IDENTIFICATIONS			
2									7	Document no			
3									8	Latest revision	Date		
4									9	Issue status			
5									10				
PERFORMANCE CHARACTERISTICS					PHYSICAL DATA								
211	Max press at design temp				246	Estimated weight							
212	Min working temperature				247	Face-to-face dimension							
213	Max pressure drop				248	Overall height							
214	Maximum starts per hour				249	Removal clearance							
215	Positioning accuracy				250	Signal conn nominal size							
216	Position accuracy rating				251	Mfr reference dwg							
217	Torque accuracy rating				252								
218	Torque adjustment LRL				253								
219	Max starting current				254								
220	Rated flow coef type				255								
221	Rated factor FI				256								
222	Rated seat leakage class				257								
223	Max valve reqd torque				258								
224	Design life cycles				259								
225	Min ambient working temp				260								
226					261								
227					262								
228					263								
229	ACCESSORIES				264								
230	Isolation switch				265								
231	Local control station				266								
232	Auxiliary power device				267								
233					268								
234					269								
235	SPECIAL REQUIREMENTS				270								
236	Custom tag				271								
237	Reference specification				272								
238	Special preparation				273								
239	Compliance standard				274								
240	Construction code				275								
241	Calculation report				276								
242	Software program				277								
243	Service design				278								
244					279								
245					280								
CALIBRATIONS AND TEST					INPUT OR TEST		OUTPUT OR SCALE						
310	TAG NO/FUNCTIONAL IDENT	MEAS/SIGNAL/SCALE	LRV	URV	ACTION	LRV	URV						
311		Position input-Travel											
312		Close sw energized-Travel											
313		Open sw energized-Travel											
314		Position-Output											
315		Torque-Output											
316		Position-Scale											
317		Aux input 1-Output											
318		Aux input 2-Output											
319		Aux input 3-Output											
320		Aux input 4-Output											
321		Position close sw-Output											
322		Position open sw-Output											
323		Torque close sw-Output											
324		Torque open sw-Output											
325		Aux output 1-Output											
326		Aux output 2-Output											
327		Aux output 3-Output											
328		Aux output 4-Output											
329		Failure signal-Output											
330													
331													
COMPONENT IDENTIFICATIONS													
332	COMPONENT TYPE			MANUFACTURER			MODEL NUMBER						
333													
334													
335													
336													
337													
338													
Rev	Date	Revision Description	By	Appv1	Appv2	Appv3	REMARKS						